

## RJ45 Series - Field Assembly RJ45

### TECHNICAL SPECIFICATIONS

<b>Material:</b>	
Contacts:	Copper Alloy w/Gold Plate
Connector Body:	PBT (Jack) or PC (Plug)
<b>Operating Temperature:</b>	-20°C to +80°C
<b>Waterproof Rating</b>	IP67 or IP68
<b>Durability:</b>	500 Cycles
<b>Flame Test:</b>	UL / CSA FT4
<b>Thermal Shock:</b>	5 cycles at -20°C to +80°C
<b>Salt Spray:</b>	48 hours



### Plug Housings



Picture:	Type:	Style:	Name:	Part No:
1	Housing with Strain Relief	Shielded / Screw Nut	RJ-00AMMA-SL7001	2640-0101-10
2	Housing with Strain Relief	Unshielded / Screw Nut	RJ-00AMMA-SL7002	2640-0101-08
3	Housing w/o Strain Relief	Unshielded / Screw Nut	RJ-00BMMA-SL7001	2640-0101-11
3	Housing w/o Strain Relief	Shielded / Screw Nut	RJ-00BMMA-SL7003	2640-0101-12
4	Housing w/o Strain Relief	Unshielded / Screw Nut	RJ-00BMMA-SL7002	2640-0101-13
5	Housing w/o Strain Relief	Shielded / Screw Nut	RJ-00BMMA-SL7004	2640-0101-09

### Plug Housings & Accessories



Picture:	Type:	Style:	Name:	Part No:
1	Housing w/o Strain Relief	Unshielded / Screw Nut	RJ-00BMMA-SL7005	2640-0101-07
2	Housing with Strain Relief	Unshielded / Bayonette	RJ-00AMMA-LL7001	2640-0101-14
2	Housing w/o Strain Relief	Unshielded / Bayonette	RJ-00BMMA-LL7001	2640-0101-15
3	Jack-to-Jack Coupler	Shielded / Screw Nut	RJS-000000-OFF-IS	<i>On Request</i>
4	Panel style Coupler with Cap	Shielded / Screw Nut	RJS-00PFFJ-SC7001	2640-0120-01
5	CAP with chain*	Unshielded / Screw Nut	CAP-WACPMSB1	2649-0101-01
5	CAP with chain*	Shielded / Screw Nut	CAP-WAFPMSB1	2649-0101-10

\* Also available with rubber lead or wire / nylon string on request.