

to DIN VDE 0623, EN 60309-2. Other voltages and frequencies available on request.






Service

Sockets

Plugs and connectors

Combination units

Special plugs and sockets, accessories

Image	Title / description	Ampere	Poles	110V	230V	400V	500V	>50 - 500V	>50 - 500V	
				50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	100 - 300 Hz	>300 - 500 Hz	
				3p 4p 5p	3p 4p 5p	3p 4p 5p	3p 4p 5p	3p 4p 5p	3p 4p 5p	
				4h 4h 4h	6h 9h 9h	9h 6h 6h	7h 7h 7h	10h 10h 10h	2h 2h 2h	
				Part numbers						
	Connector AM-TOP® with screw terminals, single part body, cable gland and sealing, strain relief and protection against kinking	16	3	509	510*	511		2441	2517	
			4	512	513	514	515	516	517	
			5	518	519	5	2026	2193	2495	
			32	3	521	522	523		2196	2674
			32	4	524	525	526	527	528	529
			32	5	530	531	6	2027	2245	2493
				* For use on camping sites, please select type 180 AC.						
	Connector ProTOP with screw terminals, cable gland and sealing, strain relief and protection against kinking, enclosure with thread lock and safety slide	16	3	179A	180A*	181A				
			4		193A	194A	195A			
			5			15A				
			32	3	121	122				
			32	4		125	126	127		
			32	5			16A			
				* For use on camping sites, please select type 180 AC.						
	Connector StarTOP® screwless, with SafeCONTACT with insulation displacement technique, cable gland and sealing, strain relief and protection against kinking, enclosure with thread lock and safety slide	16	3	979	980*					
			4		993	994	965	996		
			5			35				
			32	3	725	731				
			32	4		761	763	765		
			32	5			36			
				* For use on camping sites, please select type 180 AC.						
	Connector PowerTOP® Xtra SoftCONTACT, rubberised handle area, highly heat resistant contact carrier, frame terminals, cable gland and sealing, strain relief and protection against kinking	63	3	14101	14102					
			4		14105	14106	14107			
			5		14111	14112				
				Products with pilot contact: Part no. + index P.						
	Angled Connector with grommet	16	3		1438					
				* For use on camping sites, please select type 180 AC.						