

Panel mounted ■ with screw terminals

to DIN VDE 0623, EN 60309-2. Other voltages and frequencies available on request.

| Image | Title / description | Ampere | Poles | 110V | 230V | 400V | 500V | >50 - 500V | >50 - 500V |
|---|--|--|-------|--------------|-------------|-------------|-------------|--------------|---------------|
| | | | | 50 a. 60 Hz | 50 a. 60 Hz | 50 a. 60 Hz | 50 a. 60 Hz | 100 - 300 Hz | >300 - 500 Hz |
| | | | | 3p 4p 5p | 3p 4p 5p | 3p 4p 5p | 3p 4p 5p | 3p 4p 5p | 3p 4p 5p |
| | | | | 4h 4h 4h | 6h 9h 9h | 9h 6h 6h | 7h 7h 7h | 10h 10h 10h | 2h 2h 2h |
| | | | | Part numbers | | | | | |
|  | Panel mounted socket flange 75 x 75 mm, straight ▲ IP 44 Std. Pack. Qty: 10 Dimensions: page 12 | 16 | 3 | 1365 | 1366 | 1367 | | 3054 | 3055 |
| | | 16 | 4 | 1388 | 1389 | 1390 | 1391 | 1392 | 1393 |
| | | 16 | 5 | 1384 | 1386 | 1385 | 3057 | 3059 | 3060 |
| | | 32 | 3 | 1394 | 1395 | 1396 | | | |
| | | 32 | 4 | 1397 | 1398 | 1399 | 1400 | 1401 | 1402 |
| | | 32 | 5 | 3449 | 3454 | 3451 | 3452 | 3455 | 3447 |
|  | Panel mounted socket SoftCONTACT, flange 107 x 100 mm, straight ▲ IP 44 Std. Pack. Qty: 5 Dimensions: page 12 | 63 | 3 | 1260A | 1261A | | | | |
| | | 63 | 4 | | 1247A | 1248A | 1249A | | |
| | | 63 | 5 | | | 1252A | | | |
| | | Products with pilot contact: Part no. + index P. | | | | | | | |
|  | Panel mounted socket flange 16A, 3p: 73.5 x 64 mm, 16A 4+5p, 32A: 100 x 92 mm, 20° inclination ▲ IP 44 Std. Pack. Qty: 10 Dimensions: page 12 | 16 | 3 | 1462 | 1463 | 1464 | | 3186 | 3187 |
| | | 16 | 4 | 1465 | 1466 | 1467 | 1468 | 1469 | 1470 |
| | | 16 | 5 | 1471 | 1472 | 1473 | 3188 | 3189 | 3190 |
| | | 32 | 3 | 1491 | 1492 | 1493 | | 3201 | 3202 |
| | | 32 | 4 | 1494 | 1495 | 1496 | 1497 | 1486 | 1487 |
| | | 32 | 5 | 1498 | 1499 | 1500 | 3191 | 3192 | 3193 |
| 32A: Optionally fitted with auxiliary contact (see page 34). | | | | | | | | | |
|  | Panel mounted socket SoftCONTACT, flange 110 x 106 mm, 20° inclination ▲ IP 44 Std. Pack. Qty: 5 Dimensions: page 12 | 63 | 3 | 1146A | 1147A | 1148A | | | |
| | | 63 | 4 | 1149A | 1150A | 1151A | 1152A | | |
| | | 63 | 5 | 1153A | 1154A | 1155A | | | |
| | | Products with pilot contact: Part no. + index P. | | | | | | | |
|  | Panel mounted socket standard flange dimensions 85 x 85 mm, 20° inclination ▲ IP 44 Std. Pack. Qty: 10 Dimensions: page 12 | 16 | 3 | 3031 | 3036 | | | | |
| | | 16 | 4 | | | 3072 | 3074 | | |
| | | 16 | 5 | | | 3093 | | | |
| | | 32 | 3 | 3110 | 3112 | | 3137 | | |
| | | 32 | 4 | | 3140 | 3136 | 3114 | | |
| | | 32 | 5 | | | 3153 | | | |
| Optionally fitted with auxiliary contact (see page 34). | | | | | | | | | |
|  | Panel mounted socket 20° inclination miniflange: 68 x 62 mm ▲ IP 44 Std. Pack. Qty: 10 Dimensions: page 12 | 16 | 3 | 858 | 857 | | | | |
| | | 16 | 4 | | | | | | |
| | | 16 | 5 | | | | | | |
| | | 32 | 3 | | | | | | |
| | | 32 | 4 | | | | | | |
| | | 32 | 5 | | | | | | |

Service

Sockets

Plugs and connectors

Combination units

Special plugs and sockets,
accessories

Panel mounted ■ with screw terminals

to DIN VDE 0623, EN 60309-2. Other voltages and frequencies available on request.

Service

Sockets

Plugs and connectors

Combination units

Special plugs and sockets, accessories

| Image | Title / description | Ampere | Poles | 110V | 230V | 400V | 500V | >50 - 500V | >50 - 500V |
|---|--|--------|-------|-------------|-------------|-------------|-------------|--------------|---------------|
| | | | | 50 a. 60 Hz | 50 a. 60 Hz | 50 a. 60 Hz | 50 a. 60 Hz | 100 - 300 Hz | >300 - 500 Hz |
| | | | | 3p 4p 5p | 3p 4p 5p | 3p 4p 5p | 3p 4p 5p | 3p 4p 5p | 3p 4p 5p |
| | | | | 4h 4h 4h | 6h 9h 9h | 9h 6h 6h | 7h 7h 7h | 10h 10h 10h | 2h 2h 2h |
| Part numbers | | | | | | | | | |
|  | Panel mounted socket flange 16A: 75 x 75 mm, 32A: 85 x 75 mm, straight ⚡ IP 67 Std. Pack. Qty: 10 Dimensions: page 12 | 16 | 3 | 217A | 218A | 219A | | | |
| | | 16 | 4 | 220A | 221A | 222A | 223A | 224A | 225A |
| | | 16 | 5 | 226A | 227A | 228A | | | |
| | | 32 | 3 | 229A | 230A | 231A | | | |
| | | 32 | 4 | 232A | 233A | 234A | 235A | 236A | 237A |
| | | 32 | 5 | 238A | 239A | 240A | | | |
|  | Panel mounted socket flange 63A: 107 x 100 mm, 125A: 130 x 130 mm, straight, 63A: SoftCONTACT, 125A: TorsionSpringCONTACT ⚡ IP 67 Std. Pack. Qty: 5 Dimensions: page 12 | 63 | 3 | 1263A | 1264A | 1265A | | | |
| | | 63 | 4 | 1122A | 1123A | 1124A | 1125A | | |
| | | 63 | 5 | 1126A | 1127A | 1128A | | | |
| | | 125 | 3 | | 3380 | | | | |
| | | 125 | 4 | 1455 | 1456 | 1457 | 1458 | | |
| | | 125 | 5 | 1459 | 1460 | 1461 | 3283 | | |
| Products with pilot contact: Part no. + index P. | | | | | | | | | |
|  | Panel mounted socket flange 16A, 3p: 73.5 x 64 mm, 16A 4+5p, 32A: 100 x 92 mm, 20° inclination ⚡ IP 67 Std. Pack. Qty: 10 Dimensions: page 12 | 16 | 3 | 1474 | 1475 | 1476 | | | |
| | | 16 | 4 | 1477 | 1478 | 1479 | 1480 | 1481 | 1482 |
| | | 16 | 5 | 1483 | 1484 | 1485 | | | |
| | | 32 | 3 | 1501 | 1502 | 1503 | | | |
| | | 32 | 4 | 1504 | 1505 | 1506 | 1507 | 1567 | 1568 |
| | | 32 | 5 | 1489 | 1490 | 1551 | | | |
| 32A: Optionally fitted with auxiliary contact (see page 34). | | | | | | | | | |
|  | Panel mounted socket flange 63A: 110 x 106 mm, 20° inclination, 125A: 114 x 110 mm, 15° inclination, 63A: SoftCONTACT, 125A: TorsionSpringCONTACT ⚡ IP 67 Std. Pack. Qty: 5 Dimensions: page 12 | 63 | 3 | 2179A | 2180A | 2181A | | | |
| | | 63 | 4 | 203A | 204A | 205A | 206A | | |
| | | 63 | 5 | 207A | 208A | 209A | 3507 | | |
| | | 125 | 3 | | 3575 | | | | |
| | | 125 | 4 | 210A | 211A | 212A | 213A | | |
| | | 125 | 5 | 214A | 215A | 216A | | | |
| Products with pilot contact: Part no. + index P. | | | | | | | | | |
|  | Panel mounted socket standard flange dimensions 85 x 85 mm, 20° inclination ⚡ IP 67 Std. Pack. Qty: 10 Dimensions: page 12 | 16 | 3 | 903 | 905 | | | | |
| | | 16 | 4 | | | 1081 | 1082 | | |
| | | 16 | 5 | | | 1103 | | | |
| | | 32 | 3 | 3197 | 3200 | | | | |
| | | 32 | 4 | | | 3254 | 3256 | | |
| | | 32 | 5 | | | 3524 | | | |
| Optionally fitted with auxiliary contact (see page 34). | | | | | | | | | |
|  | Auxiliary contact Suitable for many of the standard sockets and panel mounted receptacles from 16A 3p up to 32A 5p. Std. Pack. Qty: 10 | 41000 | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |

Panel mounted ■ screwless, with TwinCONTACT

to DIN VDE 0623, EN 60309-2. Other voltages and frequencies available on request.

| Image | Title / description | Ampere | Poles | 110V | 230V | 400V | 500V | >50 - 500V | >50 - 500V | |
|---|---|--------|-------|----------------------|----------------------|----------------------|----------------------|-------------------------|----------------------|--|
| | | | | 50 a. 60 Hz | 50 a. 60 Hz | 50 a. 60 Hz | 50 a. 60 Hz | 100 - 300 Hz | >300 - 500 Hz | |
| | | | | 3p 4p 5p 4h 4h 4h | 3p 4p 5p 6h 9h 9h | 3p 4p 5p 9h 6h 6h | 3p 4p 5p 7h 7h 7h | 3p 4p 5p 10h 10h 10h | 3p 4p 5p 2h 2h 2h | |
| | | | | Part numbers | | | | | | |
|  | Panel mounted socket screwless, with TwinCONTACT, flange: 75 x 75 mm, straight ⚠ IP 44 Std. Pack. Qty: 10 Dimensions: page 12 | 16 | 3 | 1667 | 1668 | 1669 | | | 1671 | |
| | | 16 | 4 | 1672 | 1673 | 1674 | 1675 | 1676 | 1677 | |
| | | 16 | 5 | 1678 | 1679 | 3385 | 1680 | | 1682 | |
| | | 32 | 3 | 1786 | 1787 | 1788 | | | | |
| | | 32 | 4 | 1789 | 1790 | 1791 | 1792 | 1793 | 1794 | |
| | | 32 | 5 | 1795 | 1796 | 1797 | 1798 | | 1800 | |
|  | Panel mounted socket screwless, with TwinCONTACT, flange 16A, 3p: 73.5 x 64 mm, 16A, 4 + 5p, 32A: 100 x 92 mm, 20° inclination ⚠ IP 44 Std. Pack. Qty: 10 Dimensions: page 12 | 16 | 3 | 1631 | 1632 | 1633 | | | 1635 | |
| | | 16 | 4 | 1636 | 1637 | 1638 | 1639 | 1640 | 1641 | |
| | | 16 | 5 | 1642 | 1643 | 3473 | 1644 | | 1646 | |
| | | 32 | 3 | 1733 | 1734 | 1735 | | | 1737 | |
| | | 32 | 4 | 1738 | 1739 | 1740 | 1741 | 1742 | 1743 | |
| | | 32 | 5 | 1744 | 1745 | 1746 | 1747 | | 1749 | |
| 32A: Optionally fitted with auxiliary contact (see page 34). | | | | | | | | | | |
|  | Panel mounted socket screwless, with TwinCONTACT, standard flange dimensions 85 x 85 mm, 20° inclination ⚠ IP 44 Std. Pack. Qty: 10 Dimensions: page 12 | 16 | 3 | 3004 | 3008 | | | | | |
| | | 16 | 4 | | | 3048 | 3049 | | | |
| | | 16 | 5 | | | 3070 | | | | |
| | | 32 | 3 | 3124 | 3126 | | | | | |
| | | 32 | 4 | | | 3155 | 3157 | | | |
| | | 32 | 5 | | | 3171 | | | | |
| Optionally fitted with auxiliary contact (see page 34). | | | | | | | | | | |
|  | Panel mounted socket screwless, with TwinCONTACT, mini flange 55 x 55 mm, straight ⚠ IP 44 Std. Pack. Qty: 10 Dimensions: page 12 | 16 | 3 | 1618 | 1619 | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
|  | Panel mounted socket RAPIDO® , screwless, with TwinCONTACT with central locking system, round flange for central fixing, diam. 61 mm ⚠ IP 44 Std. Pack. Qty: 10 Dimensions: page 13 | 16 | 3 | 1132 | 997 | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
|  | Panel mounted socket RAPIDO® , screwless, with TwinCONTACT with central locking system, round flange for central fixing, diam. 70 mm ⚠ IP 44 Std. Pack. Qty: 10 Dimensions: page 13 | 16 | 4 | | 1133 | 998 | 1134 | | | |
| | | 16 | 5 | | | 907 | | | | |
| | | 32 | 3 | 1135 | 987 | | | | | |
| | | 32 | 4 | | 1166 | 988 | 1167 | | | |
| | | 32 | 5 | | | 989 | | | | |
| | | | | | | | | | | |

Service

Sockets

Plugs and connectors

Combination units

Special plugs and sockets,
accessories

Panel mounted ■ screwless, with TwinCONTACT

to DIN VDE 0623, EN 60309-2. Other voltages and frequencies available on request.





Service


Sockets

Plugs and connectors

Combination units

Special plugs and sockets, accessories

| Image | Title / description | Ampere | Poles | 110V | 230V | 400V | 500V | >50 - 500V | >50 - 500V |
|---|--|--------|-------|-------------|-------------|-------------|-------------|--------------|---------------|
| | | | | 50 a. 60 Hz | 50 a. 60 Hz | 50 a. 60 Hz | 50 a. 60 Hz | 100 - 300 Hz | >300 - 500 Hz |
|  <p>Panel mounted socket screwless, with TwinCONTACT, flange: 16A: 75 x 75 mm, 32A: 85 x 75 mm, straight</p> <p>⚡ IP 67 Std. Pack. Qty: 10 Dimensions: page 12</p> | 16 | 3 | 1707 | 1708 | 1709 | | | | |
| | 16 | 4 | 1710 | 1711 | 1712 | 1713 | 1714 | 1715 | |
| | 16 | 5 | 1716 | 1717 | 1131 | | | | |
| | 32 | 3 | 1809 | 1810 | 1811 | | | | |
| | 32 | 4 | 1812 | 1813 | 1814 | 1815 | 1816 | 1817 | |
| | 32 | 5 | 1818 | 1819 | 1820 | | | | |
| | Part numbers | | | | | | | | |
|  <p>Panel mounted socket screwless, with TwinCONTACT, flange: 16A, 3p: 73.5 x 64 mm, 16A, 4 + 5p, 32A: 100 x 92 mm, 20° inclination</p> <p>⚡ IP 67 Std. Pack. Qty: 10 Dimensions: page 12</p> | 16 | 3 | 1700 | 1701 | 1702 | | | | |
| | 16 | 4 | | 1703 | 1704 | 1705 | 1706 | | |
| | 16 | 5 | | | 3485 | | | | |
| | 32 | 3 | 1801 | 1802 | 1803 | | | | |
| | 32 | 4 | | 1804 | 1805 | 1806 | 1807 | | |
| | 32 | 5 | | | 1808 | | | | |
| | 32A: Optionally fitted with auxiliary contact. | | | | | | | | |
|  <p>Panel mounted socket screwless, with TwinCONTACT, standard flange dimensions 85 x 85 mm, 20° inclination</p> <p>⚡ IP 67 Std. Pack. Qty: 10 Dimensions: page 12</p> | 16 | 3 | 1158 | 1168 | | | | | |
| | 16 | 4 | | | 1169 | 1171 | | | |
| | 16 | 5 | | | 1173 | | | | |
| | 32 | 3 | 3566 | 3573 | | | | | |
| | 32 | 4 | | | 3581 | 3587 | | | |
| | 32 | 5 | | | 3590 | | | | |
| | Optionally fitted with auxiliary contact. | | | | | | | | |
|  <p>Auxiliary contact Suitable for many of the standard sockets and panel mounted receptacles from 16A 3p up to 32A 5p.</p> <p>Std. Pack. Qty: 10</p> | 41000 | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |



Auxiliary contact



Function: Change-over contact = NC/NO

Connected load: 16A (4A)* / ~ 250V
10A (3A)* / ~ 400V

*for inductive or motor load

Panel mounted, switched and interlocked

to DIN VDE 0623, EN 60309-2. Other voltages and frequencies available on request.

| Image | Title / description | Ampere | Poles | 110V | 230V | 400V | 500V | >50 - 500V | >50 - 500V |
|---|---------------------|---------------------|-------|----------------------|----------------------|----------------------|----------------------|-------------------------|----------------------|
| | | | | 50 a. 60 Hz | 50 a. 60 Hz | 50 a. 60 Hz | 50 a. 60 Hz | 100 - 300 Hz | >300 - 500 Hz |
| | | | | 3p 4p 5p 4h 4h 4h | 3p 4p 5p 6h 9h 9h | 3p 4p 5p 9h 6h 6h | 3p 4p 5p 7h 7h 7h | 3p 4p 5p 10h 10h 10h | 3p 4p 5p 2h 2h 2h |
| | | Part numbers | | | | | | | |
|  <p>Panel mounted socket switched, with mechanical DUO-interlock</p> <p>⚠ IP 44 Std. Pack. Qty: 1 Dimensions: page 13</p> | 16 | 3 | 7502 | 7503 | | | | | |
| | 16 | 4 | | 7504 | 7505 | 7506 | | | |
| | 16 | 5 | | | 7507 | | | | |
| | 32 | 3 | 7511 | 7512 | | | | | |
| | 32 | 4 | | 7513 | 7514 | 7515 | | | |
| | 32 | 5 | | | 7516 | | | | |
| | | | | | | | | | |
|  <p>Panel mounted socket switched, with mechanical DUO-interlock</p> <p>⚡ IP 67 Std. Pack. Qty: 1 Dimensions: page 13</p> | 16 | 3 | 7520 | 7521 | | | | | |
| | 16 | 4 | | 7523 | 7524 | 7525 | | | |
| | 16 | 5 | | | 7526 | | | | |
| | 32 | 3 | 7530 | 7531 | | | | | |
| | 32 | 4 | | 7533 | 7534 | 7535 | | | |
| | 32 | 5 | | | 7536 | | | | |
| | | | | | | | | | |

Service

Sockets

Plugs and connectors

Combination units

Special plugs and sockets,
accessories