



Material	INOX 1.4404
Seal	VMQ (silicone)
Protection class	IP 69 K / IP 68 – 10 bar / IP 66
Temperature range	-40°C to +120°C

**EMV
EMC**

- // EMC connection integrated
- // VDMA Riboflavin cleaning test passed
- // EHEDG O1 cleaning test passed
- // EHEDG certificate EL class I AUX approved

AG	Ø* mm	D mm	GL mm	H mm	SW1/SW2 mm	⌀ Nm	Item-No
M12 x 1.5	5 – 6.5	21	6	19	14/14	8	1.740.1203.50
M16 x 1.5	6 – 7.5	27	6	20	19/21	15	1.740.1603.51
M16 x 1.5	7.5 – 10	27	6	20	19/21	15	1.740.1603.50
M20 x 1.5	9 – 12	33	6	22.5	24/27	30	1.740.2003.51
M20 x 1.5	11 – 13.5	33	6	22.5	24/27	30	1.740.2003.50
M25 x 1.5	14 – 16	38	7	23.5	30/30	35	1.740.2503.52
M25 x 1.5	15 – 18	38	7	23.5	30/30	35	1.740.2503.50
M32 x 1.5	18 – 21	45	8	26.5	36/36	40	1.740.3203.51
M32 x 1.5	21 – 25	45	8	26.5	36/36	40	1.740.3203.50



to the assembly
instruction

