



|                   |                     |
|-------------------|---------------------|
| Material          | Nickel-plated brass |
| Seal              | FKM                 |
| Material o-ring   | FKM                 |
| Protection class  | IP 68 – 10 bar      |
| Temperature range | -20°C to +180°C     |

RoHS

EMV  
EMC

- // High resistance to acids and chemicals
- // Integrated possibility for EMC connection
- // Large clamping range through reduction insert
- // Integrated anti-twist protection during cable installation

| AG        | Øk<br>mm  | GL<br>mm | H<br>mm | SW1/SW2<br>mm | Nm | Item-No       |
|-----------|-----------|----------|---------|---------------|----|---------------|
| M12 x 1.5 | 2 – 8     | 6.5      | 20      | 16/17         | 3  | 1.752.1200.50 |
| M12 x 1.5 | 5 – 8     | 6.5      | 20      | 16/17         | 5  | 1.752.1200.51 |
| M16 x 1.5 | 4 – 11    | 7        | 24.5    | 19/20         | 5  | 1.752.1600.50 |
| M16 x 1.5 | 7 – 11    | 7        | 24.5    | 19/20         | 8  | 1.752.1600.51 |
| M20 x 1.5 | 7 – 14    | 6        | 27      | 22/24         | 6  | 1.752.2000.50 |
| M20 x 1.5 | 10 – 14   | 6        | 27      | 22/24         | 6  | 1.752.2000.51 |
| M25 x 1.5 | 11 – 18   | 7        | 29      | 27/30         | 10 | 1.752.2500.50 |
| M25 x 1.5 | 14.5 – 18 | 7        | 29      | 27/30         | 10 | 1.752.2500.51 |
| M32 x 1.5 | 16 – 25   | 8        | 34      | 36/40         | 12 | 1.752.3200.50 |
| M32 x 1.5 | 20.5 – 25 | 8        | 34      | 36/40         | 12 | 1.752.3200.51 |
| M40 x 1.5 | 21 – 32   | 8        | 40      | 46/50         | 15 | 1.752.4000.50 |
| M40 x 1.5 | 26.5 – 32 | 8        | 40      | 46/50         | 15 | 1.752.4000.51 |
| M50 x 1.5 | 31 – 42   | 9        | 48      | 57/57         | 20 | 1.752.5000.50 |
| M50 x 1.5 | 35 – 42   | 9        | 48      | 57/57         | 20 | 1.752.5000.51 |
| M63 x 1.5 | 41 – 54   | 10       | 47.5    | 65/68         | 32 | 1.752.6300.50 |
| M63 x 1.5 | 46.5 – 54 | 10       | 47.5    | 65/68         | 37 | 1.752.6300.51 |