



Material	Nickel-plated brass
Seal	EPDM
Material o-ring	EPDM
Protection class	IP 68 – 10 bar
Integrity	E30 / E20
Temperature range	-40°C to +100°C

RoHS

EMV
EMC

- // DIN EN 45545-2 and DIN EN 45545-3
- // Large clamping range through reduction insert
- // Integrated anti-twist protection during cable installation

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	Nm	Item-No
M12 x 1.5	2 – 8	6.5	20	16/17	3	1.750.1200.50
M12 x 1.5	5 – 8	6.5	20	16/17	5	1.750.1200.51
M16 x 1.5	4 – 11	7	24.5	19/20	5	1.750.1600.50
M16 x 1.5	7 – 11	7	24.5	19/20	8	1.750.1600.51
M20 x 1.5	7 – 14	6	27	22/24	6	1.750.2000.50
M20 x 1.5	10 – 14	6	27	22/24	6	1.750.2000.51
M25 x 1.5	11 – 18	7	29	27/30	10	1.750.2500.50
M25 x 1.5	14.5 – 18	7	29	27/30	10	1.750.2500.51
M32 x 1.5	16 – 25	8	34	36/40	12	1.750.3200.50
M32 x 1.5	20.5 – 25	8	34	36/40	12	1.750.3200.51
M40 x 1.5	21 – 32	8	40	46/50	15	1.750.4000.50
M40 x 1.5	26.5 – 32	8	40	46/50	15	1.750.4000.51
M50 x 1.5	31 – 42	9	48	57/57	20	1.750.5000.50
M50 x 1.5	35 – 42	9	48	57/57	20	1.750.5000.51
M63 x 1.5	41 – 54	10	47.5	65/68	32	1.750.6300.50
M63 x 1.5	46.5 – 54	10	47.5	65/68	37	1.750.6300.51



to the product video

