

Panel mounted inlets

to DIN VDE 0623, EN 60309-2. Other voltages and frequencies available on request.

Image	Title / description	Ampere	Poles	110V	230V	400V	500V	>50 - 500V	>50 - 500V
				50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	100 - 300 Hz	>300 - 500 Hz
				3p 4p 5p 4h 4h 4h	3p 4p 5p 6h 9h 9h	3p 4p 5p 9h 6h 6h	3p 4p 5p 7h 7h 7h	3p 4p 5p 10h 10h 10h	3p 4p 5p 2h 2h 2h
Part numbers									
	Panel mounted inlet 16A: flange 66 x 66 mm, fixing distance 52 x 52 mm 32A: flange 72 x 72 mm, fixing distance 60 x 60 mm ⚠ IP 44 Std. Pack. Qty: 10 Dimensions: page 14	16	5			1408			
		32	5			1409			
A retaining device to match the hinged lid of the connector must be provided to ensure the latching feature.									
	Panel mounted inlet flange 75 x 75 mm, fixing distance 60 x 60 mm ⚠ IP 44 Std. Pack. Qty: 10 Dimensions: page 14	16	5			853			
A retaining device to match the hinged lid of the connector must be provided to ensure the latching feature.									
	Panel mounted inlet with nickel plated contacts ⚠ IP 44 Std. Pack. Qty: 10 Dimensions: page 14	16	3	810	812				
		16	4		837	813	814		
		16	5			815			
		32	3	816	817				
		32	4		838	819	820		
		32	5			821			
		A retaining device to match the hinged lid of the connector must be provided to ensure the latching feature.							
	Panel mounted inlet with highly heat resistant contact carrier and nickel plated contacts ⚠ IP 44 Std. Pack. Qty: 5 Dimensions: page 14	63	3	822	1981				
		63	4		1984	1982	824		
		63	5			1688			
A retaining device to match the hinged lid of the connector must be provided to ensure the latching feature.									
	Panel mounted inlet with nickel plated contacts ⚠ IP 67 Std. Pack. Qty: 10 Dimensions: page 14	16	3	825	826				
		16	4		839	827	828		
		16	5			829			
		32	3	830	831				
		32	4		840	832	833		
		32	5			834			
		A retaining device to match the hinged lid of the connector must be provided to ensure the latching feature.							
	Panel mounted inlet with highly heat resistant contact carrier and nickel plated contacts ⚠ IP 67 Std. Pack. Qty: 5 Dimensions: page 14	63	3	835	836				
		63	4		3704	3656	3657		
		63	5			3658			
		125	3		3665				
		125	4		3413	3583	3600		
		125	5			1983			
		63A: A retaining device to match the hinged lid of the connector must be provided to ensure the latching feature							

Service

Sockets

Plugs and connectors

Combination units

Special plugs and sockets,
accessories