

Panel mounted ■ with screw terminals

to DIN VDE 0623, EN 60309-2. Other voltages and frequencies available on request.

Image	Title / description	Ampere	Poles	110V	230V	400V	500V	>50 - 500V	>50 - 500V
				50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	100 - 300 Hz	>300 - 500 Hz
				3p 4p 5p 4h 4h 4h	3p 4p 5p 6h 9h 9h	3p 4p 5p 9h 6h 6h	3p 4p 5p 7h 7h 7h	3p 4p 5p 10h 10h 10h	3p 4p 5p 2h 2h 2h
Part numbers									
	Panel mounted socket flange 75 x 75 mm, straight ⚠ IP 44 Std. Pack. Qty: 10 Dimensions: page 12	16	3	1365	1366	1367		3054	3055
		16	4	1388	1389	1390	1391	1392	1393
		16	5	1384	1386	1385	3057	3059	3060
		32	3	1394	1395	1396			
		32	4	1397	1398	1399	1400	1401	1402
		32	5	3449	3454	3451	3452	3455	3447
	Panel mounted socket SoftCONTACT, flange 107 x 100 mm, straight ⚠ IP 44 Std. Pack. Qty: 5 Dimensions: page 12	63	3	1260A	1261A				
		63	4		1247A	1248A	1249A		
		63	5			1252A			
Products with pilot contact: Part no. + index P.									
	Panel mounted socket flange 16A, 3p: 73.5 x 64 mm, 16A 4+5p, 32A: 100 x 92 mm, 20° inclination ⚠ IP 44 Std. Pack. Qty: 10 Dimensions: page 12	16	3	1462	1463	1464		3186	3187
		16	4	1465	1466	1467	1468	1469	1470
		16	5	1471	1472	1473	3188	3189	3190
		32	3	1491	1492	1493		3201	3202
		32	4	1494	1495	1496	1497	1486	1487
		32	5	1498	1499	1500	3191	3192	3193
32A: Optionally fitted with auxiliary contact (see page 34).									
	Panel mounted socket SoftCONTACT, flange 110 x 106 mm, 20° inclination ⚠ IP 44 Std. Pack. Qty: 5 Dimensions: page 12	63	3	1146A	1147A	1148A			
		63	4	1149A	1150A	1151A	1152A		
		63	5	1153A	1154A	1155A			
Products with pilot contact: Part no. + index P.									
	Panel mounted socket standard flange dimensions 85 x 85 mm, 20° inclination ⚠ IP 44 Std. Pack. Qty: 10 Dimensions: page 12	16	3	3031	3036				
		16	4			3072	3074		
		16	5			3093			
		32	3	3110	3112		3137		
		32	4		3140	3136	3114		
		32	5			3153			
Optionally fitted with auxiliary contact (see page 34).									
	Panel mounted socket 20° inclination miniflange: 68 x 62 mm ⚠ IP 44 Std. Pack. Qty: 10 Dimensions: page 12	16	3	858	857				
		16	4						
		16	5						
		32	3						
		32	4						
		32	5						

Service

Sockets

Plugs and connectors

Combination units

Special plugs and sockets,
accessories

Panel mounted ■ with screw terminals

to DIN VDE 0623, EN 60309-2. Other voltages and frequencies available on request.

Image	Title / description	Ampere	Poles	110V	230V	400V	500V	>50 - 500V	>50 - 500V
				50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	100 - 300 Hz	>300 - 500 Hz
				3p 4p 5p 4h 4h 4h	3p 4p 5p 6h 9h 9h	3p 4p 5p 9h 6h 6h	3p 4p 5p 7h 7h 7h	3p 4p 5p 10h 10h 10h	3p 4p 5p 2h 2h 2h
				Part numbers					
	Panel mounted socket flange 16A: 75 x 75 mm, 32A: 85 x 75 mm, straight ♦♦ IP 67 Std. Pack. Qty: 10 Dimensions: page 12	16	3	217A	218A	219A			
		16	4	220A	221A	222A	223A	224A	225A
		16	5	226A	227A	228A			
		32	3	229A	230A	231A			
		32	4	232A	233A	234A	235A	236A	237A
		32	5	238A	239A	240A			
	Panel mounted socket flange 63A: 107 x 100 mm, 125A: 130 x 130 mm, straight, 63A: SoftCONTACT, 125A: TorsionSpringCONTACT ♦♦ IP 67 Std. Pack. Qty: 5 Dimensions: page 12	63	3	1263A	1264A	1265A			
		63	4	1122A	1123A	1124A	1125A		
		63	5	1126A	1127A	1128A			
		125	3		3380				
		125	4	1455	1456	1457	1458		
		125	5	1459	1460	1461	3283		
				Products with pilot contact: Part no. + index P.					
	Panel mounted socket flange 16A, 3p: 73.5 x 64 mm, 16A 4+5p, 32A: 100 x 92 mm, 20° inclination ♦♦ IP 67 Std. Pack. Qty: 10 Dimensions: page 12	16	3	1474	1475	1476			
		16	4	1477	1478	1479	1480	1481	1482
		16	5	1483	1484	1485			
		32	3	1501	1502	1503			
		32	4	1504	1505	1506	1507	1567	1568
		32	5	1489	1490	1551			
				32A: Optionally fitted with auxiliary contact (see page 34).					
	Panel mounted socket flange 63A: 110 x 106 mm, 20° inclination, 125A: 114 x 110 mm, 15° inclination, 63A: SoftCONTACT, 125A: TorsionSpringCONTACT ♦♦ IP 67 Std. Pack. Qty: 5 Dimensions: page 12	63	3	2179A	2180A	2181A			
		63	4	203A	204A	205A	206A		
		63	5	207A	208A	209A	3507		
		125	3		3575				
		125	4	210A	211A	212A	213A		
		125	5	214A	215A	216A			
				Products with pilot contact: Part no. + index P.					
	Panel mounted socket standard flange dimensions 85 x 85 mm, 20° inclination ♦♦ IP 67 Std. Pack. Qty: 10 Dimensions: page 12	16	3	903	905				
		16	4			1081	1082		
		16	5			1103			
		32	3	3197	3200				
		32	4			3254	3256		
		32	5			3524			
				Optionally fitted with auxiliary contact (see page 34).					
	Auxiliary contact Suitable for many of the standard sockets and panel mounted receptacles from 16A 3p up to 32A 5p. Std. Pack. Qty: 10	41000							

Panel mounted ■ screwless, with TwinCONTACT

to DIN VDE 0623, EN 60309-2. Other voltages and frequencies available on request.

Image	Title / description	Ampere	Poles	110V	230V	400V	500V	>50 - 500V	>50 - 500V
				50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	100 - 300 Hz	>300 - 500 Hz
				3p 4p 5p 4h 4h 4h	3p 4p 5p 6h 9h 9h	3p 4p 5p 9h 6h 6h	3p 4p 5p 7h 7h 7h	3p 4p 5p 10h 10h 10h	3p 4p 5p 2h 2h 2h
Part numbers									
	Panel mounted socket screwless, with TwinCONTACT, flange: 75 x 75 mm, straight ⚠ IP 44 Std. Pack. Qty: 10 Dimensions: page 12	16	3	1667	1668	1669			1671
		16	4	1672	1673	1674	1675	1676	1677
		16	5	1678	1679	3385	1680		1682
		32	3	1786	1787	1788			
		32	4	1789	1790	1791	1792	1793	1794
		32	5	1795	1796	1797	1798		1800
	Panel mounted socket screwless, with TwinCONTACT, flange 16A, 3p: 73.5 x 64 mm, 16A, 4 + 5p, 32A: 100 x 92 mm, 20° inclination ⚠ IP 44 Std. Pack. Qty: 10 Dimensions: page 12	16	3	1631	1632	1633			1635
		16	4	1636	1637	1638	1639	1640	1641
		16	5	1642	1643	3473	1644		1646
		32	3	1733	1734	1735			1737
		32	4	1738	1739	1740	1741	1742	1743
		32	5	1744	1745	1746	1747		1749
32A: Optionally fitted with auxiliary contact (see page 34).									
	Panel mounted socket screwless, with TwinCONTACT, standard flange dimensions 85 x 85 mm, 20° inclination ⚠ IP 44 Std. Pack. Qty: 10 Dimensions: page 12	16	3	3004	3008				
		16	4			3048	3049		
		16	5			3070			
		32	3	3124	3126				
		32	4			3155	3157		
		32	5			3171			
Optionally fitted with auxiliary contact (see page 34).									
	Panel mounted socket screwless, with TwinCONTACT, mini flange 55 x 55 mm, straight ⚠ IP 44 Std. Pack. Qty: 10 Dimensions: page 12	16	3	1618	1619				
	Panel mounted socket RAPIDO® , screwless, with TwinCONTACT with central locking system, round flange for central fixing, diam. 61 mm ⚠ IP 44 Std. Pack. Qty: 10 Dimensions: page 13	16	3	1132	997				
	Panel mounted socket RAPIDO® , screwless, with TwinCONTACT with central locking system, round flange for central fixing, diam. 70 mm ⚠ IP 44 Std. Pack. Qty: 10 Dimensions: page 13	16	4		1133	998	1134		
		16	5			907			
		32	3	1135	987				
		32	4		1166	988	1167		
		32	5			989			

Service

Sockets

Plugs and connectors

Combination units

Special plugs and sockets,
accessories

Panel mounted ■ screwless, with TwinCONTACT

to DIN VDE 0623, EN 60309-2. Other voltages and frequencies available on request.

Image	Title / description	Ampere	Poles	110V	230V	400V	500V	>50 - 500V	>50 - 500V
				50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	100 - 300 Hz	>300 - 500 Hz
Part numbers									
	Panel mounted socket screwless, with TwinCONTACT, flange: 16A: 75 x 75 mm, 32A: 85 x 75 mm, straight ⚡ IP 67 Std. Pack. Qty: 10 Dimensions: page 12	16	3	1707	1708	1709			
		16	4	1710	1711	1712	1713	1714	1715
		16	5	1716	1717	1131			
		32	3	1809	1810	1811			
		32	4	1812	1813	1814	1815	1816	1817
		32	5	1818	1819	1820			
	Panel mounted socket screwless, with TwinCONTACT, flange: 16A, 3p: 73.5 x 64 mm, 16A, 4 + 5p, 32A: 100 x 92 mm, 20° inclination ⚡ IP 67 Std. Pack. Qty: 10 Dimensions: page 12	16	3	1700	1701	1702			
		16	4		1703	1704	1705	1706	
		16	5			3485			
		32	3	1801	1802	1803			
		32	4		1804	1805	1806	1807	
		32	5			1808			
32A: Optionally fitted with auxiliary contact.									
	Panel mounted socket screwless, with TwinCONTACT, standard flange dimensions 85 x 85 mm, 20° inclination ⚡ IP 67 Std. Pack. Qty: 10 Dimensions: page 12	16	3	1158	1168				
		16	4			1169	1171		
		16	5			1173			
		32	3	3566	3573				
		32	4			3581	3587		
		32	5			3590			
Optionally fitted with auxiliary contact.									
	Auxiliary contact Suitable for many of the standard sockets and panel mounted receptacles from 16A 3p up to 32A 5p. Std. Pack. Qty: 10	41000							
	Auxiliary contact Function: Change-over contact = NC/NO Connected load: 16A (4A)*/ ~ 250V 10A (3A)*/ ~ 400V *for inductive or motor load								

Panel mounted, switched and interlocked

to DIN VDE 0623, EN 60309-2. Other voltages and frequencies available on request.

Image	Title / description	Ampere	Poles	110V	230V	400V	500V	>50 - 500V	>50 - 500V
				50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	100 - 300 Hz	>300 - 500 Hz
				3p 4p 5p 4h 4h 4h	3p 4p 5p 6h 9h 9h	3p 4p 5p 9h 6h 6h	3p 4p 5p 7h 7h 7h	3p 4p 5p 10h 10h 10h	3p 4p 5p 2h 2h 2h
Part numbers									
	Panel mounted socket switched, with mechanical DUO-interlock ⚠ IP 44 Std. Pack. Qty: 1 Dimensions: page 13	16	3	7502	7503				
		16	4		7504	7505	7506		
		16	5			7507			
		32	3	7511	7512				
		32	4		7513	7514	7515		
		32	5			7516			
	Panel mounted socket switched, with mechanical DUO-interlock ⚡ IP 67 Std. Pack. Qty: 1 Dimensions: page 13	16	3	7520	7521				
		16	4		7523	7524	7525		
		16	5			7526			
		32	3	7530	7531				
		32	4		7533	7534	7535		
		32	5			7536			

Service

Sockets

Plugs and connectors

Combination units

Special plugs and sockets,
accessories